

1 repeating said preparing and said sending until an entire XML document is  
2 sent to a client.

3  
4 2. The method of claim 1, wherein said preparing comprises:  
5 gathering data that is to appear in the XML document;  
6 calling an emitter object;  
7 passing the emitter object gathered data; and  
8 formatting the gathered data into an appropriate XML syntax with the  
9 emitter object.

10  
11 3. The method of claim 2, wherein said gathering comprises using a  
12 data gathering object to gather said data.

13  
14 4. The method of claim 1 further comprising prior to said preparing,  
15 receiving a request for the XML document from the client.

16  
17 5. A method of responding to an Extensible Markup Language (XML)  
18 request comprising:

19 receiving an XML request from a client;  
20 preparing only a portion of a response to the request; and  
21 sending the response portion to the client.

22  
23 6. The method of claim 5 further comprising repeating said preparing  
24 and said sending until an entire response has been sent to the client.  
25

1           7.     The method of claim 5 further comprising repeating said preparing  
2 and said sending until an entire response has been sent to the client, said preparing  
3 of response portions taking place in a defined order.

4  
5           8.     The method of claim 5 further comprising repeating said preparing  
6 and said sending until an entire response has been sent to the client, said preparing  
7 of response portions taking place in a defined order, wherein the response  
8 comprises an XML multistatus response.

9  
10          9.     The method of claim 5, wherein the response comprises an XML  
11 multistatus response.

12  
13          10.    The method of claim 5, wherein said preparing comprises:  
14 gathering data for said response portion with a data-gathering mechanism;  
15 and  
16 formatting gathered data into an appropriate XML syntax with a data-  
17 formatting mechanism.

18  
19          11.    The method of claim 10, wherein said sending comprises sending the  
20 response portion to the client with a response-sending mechanism.

21  
22          12.    The method of claim 11, wherein said response-sending mechanism  
23 includes a buffer for holding at least one response portion that is prepared by the  
24 data-formatting mechanism and further comprising:  
25 defining a buffer threshold;

1 buffering said at least one response portion in the buffer; and  
2 sending said at least one response portion to the client when the buffer  
3 threshold is reached.

4  
5 13. A computer-readable medium having a program which, when  
6 executed by a computer, performs the method of claim 5.

7  
8 14. (Amended) A method of responding to an Extensible Markup  
9 Language (XML) request comprising:

10 receiving an XML request from a client;  
11 gathering data that is to appear in a response to the client's request;  
12 calling an emitter object and passing the emitter object the gathered data;  
13 formatting the gathered data into an appropriate XML syntax with the  
14 emitter object; and

15 emitting formatted data from the emitter object, the emitter object emitting  
16 the formatted data in a manner in which an XML response can be sent to the client  
17 without having to build a hierarchical tree that represents the XML response.

18  
19 15. The method of claim 14 further comprising:  
20 accumulating the emitted formatted data in a buffer; and  
21 sending buffered data to the client when the buffer contains a defined  
22 amount of data that is less than an amount that would constitute a complete  
23 response to the client's request.

24  
25 16. The method of claim 14, wherein:

1 said calling comprises calling the emitter object multiple times; and  
2 said emitting comprises emitting multiple amounts of formatted data.

3  
4 17. The method of claim 14, wherein:

5 said calling comprises calling the emitter object multiple times and in a  
6 defined order; and

7 said emitting comprises emitting multiple amounts of formatted data.

8  
9 18. The method of claim 14, wherein said gathering comprises gathering  
10 data that is to appear in a multistatus response.

11  
12 19. A computer-readable medium having a program which, when  
13 executed by a computer, performs the method of claim 14.

14  
15 20. A method of responding to an Extensible Markup Language (XML)  
16 request comprising:

17 receiving an XML request from a client; the XML request containing a  
18 Web Distributed Authoring and Versioning (WebDAV) request method;

19 determining the WebDAV request method that is contained in the client's  
20 request;

21 creating a request method object for the WebDAV request method;

22 gathering data that is to appear in a response to the client's request with the  
23 request method object;

24 calling an emitter object and passing the emitter object data that was  
25 gathered by the request method object; and

1 generating at least a portion of a syntactically correct XML response with  
2 the emitter object using the data that was gathered by the request method object.

3  
4 21. The method of claim 20 further comprising sending the response  
5 portion to the client.

6  
7 22. The method of claim 21, wherein the sending of the response portion  
8 comprises doing so without building an entire hierarchical tree structure that  
9 represents an entire response for the client's request.

10  
11 23. The method of claim 20, wherein said calling comprises calling the  
12 emitter object a plurality of times for a given response.

13  
14 24. The method of claim 20, wherein said generating comprises  
15 generating a plurality of syntactically correct XML response portions and sending  
16 said response portions separately to the client.

17  
18 25. The method of claim 20, wherein said calling comprises calling the  
19 emitter object a plurality of times and in a defined order for a given response.

20  
21 26. The method of claim 20, wherein:  
22 said calling comprises calling the emitter object a plurality of times for a  
23 given response; and  
24 said generating comprises generating a plurality of syntactically correct  
25 XML response portions and sending said response portions separately to the client.

1  
2 27. The method of claim 20 further comprising:  
3 buffering a plurality of response portions in a buffer; and  
4 sending the plurality of response portions together to the client.  
5

6 28. The method of claim 27, wherein said sending of the plurality of  
7 response portions comprises sending less than an entirety of a response to the  
8 client.  
9

10 29. The method of claim 27 further comprising:  
11 setting a threshold value on the buffer;  
12 determining when the threshold value is satisfied by the response portions  
13 that are buffered therein; and  
14 responsive to the threshold value being satisfied, sending the buffered  
15 response portions to the client.  
16

17 30. A computer-readable medium having a program which, when  
18 executed by a computer, performs the method of claim 20.  
19

20 31. An Extensible Markup Language (XML) request processor  
21 comprising:  
22 an XML response generator comprising:  
23 a request-receiving mechanism configured to receive an XML request from  
24 a client;  
25

1 a response-preparing mechanism coupled with the request-receiving  
2 mechanism and configured to prepare only a portion of a response at a time; and  
3 a sending mechanism coupled with the response-preparing mechanism and  
4 configured to receive response portions from the response-preparing mechanism  
5 and to send the response portions to the client, the sent response portions  
6 constituting less than an entirety of a response.

7  
8 32. The XML request processor of claim 31, wherein the response-  
9 preparing mechanism is configured to prepare response portions and the sending  
10 mechanism is configured to send the response portions to the client until an entire  
11 response is sent to the client.

12  
13 33. The XML request processor of claim 31, wherein the response that is  
14 sent to the client comprises a multistatus response.

15  
16 34. The XML request processor of claim 31, wherein the response-  
17 preparing mechanism is configured to prepare response portions in a defined  
18 order.

19  
20 35. The XML request processor of claim 31, wherein the response-  
21 preparing mechanism includes a data-gathering function that gathers data that is to  
22 appear in a client's response, and a formatting function that receives data that is  
23 gathered by the data-gathering function and formats the data into an appropriate  
24 XML syntax.  
25

1           36. The XML request processor of claim 31, wherein the sending  
2 mechanism includes a buffer for buffering response portions that are received  
3 from the response-preparing mechanism, and wherein the buffer has a defined  
4 threshold which, when satisfied, enables the sending mechanism to send buffered  
5 response portions to the client.

6  
7           37. An Extensible Markup Language (XML) request processor  
8 comprising:

9           a data-gathering object for gathering data that is to appear in a client  
10 response and generating calls in a predefined order that contain the gathered data;  
11 and

12           an emitter object configured to receive calls that are generated by the data-  
13 gathering object and format the data contained therein into an appropriate XML  
14 syntax.

15  
16           38. The XML request processor of claim 37, wherein the emitter object  
17 is configured to emit only portions of a response that are piecewise sent to the  
18 client.

19  
20           39. The XML request processor of claim 38 further comprising a buffer  
21 that is configured to receive response portions that are emitted from the emitter  
22 object, buffered response portions being sent to the client when a defined buffer  
23 threshold is satisfied.



1        40. The XML request processor of claim 37 further comprising a buffer  
2 that is configured to receive response portions that are emitted from the emitter  
3 object, buffered response portions being accumulated by the buffer and sent to the  
4 client when a defined buffer threshold is satisfied, the buffered response portions  
5 comprising less than a complete response.

6  
7        41. A computer-readable medium having a computer program for  
8 responding to an XML request, the program comprising the following steps:

9        receiving a client request;

10       determining an HTTP verb that is contained in the client request;

11       instantiating a request method object that corresponds to the HTTP verb  
12 that is contained in the client request;

13       using the request method object to gather information that is to appear in a  
14 response to the client's request;

15       making a series of calls to an emitter object that is configured to receive  
16 information from the request method object and process the information into a  
17 response portion having an appropriate XML syntactic format; and

18       sending the response portion to the client.

19  
20       42. The program of claim 41, wherein the making of the series of calls  
21 comprises doing so in a defined order.

22  
23       43. The program of claim 41 further comprising accumulating response  
24 portions, said sending comprising sending accumulated response portions to the  
25

1 client, the accumulated response portions constituting less than an entirety of a  
2 complete client response.

3  
4 44. A computer-readable medium having software code that is  
5 configured to receive an XML request from a client and instantiate an object that  
6 corresponds to an HTTP verb that is contained in the request, the software code  
7 further using the object to build a portion of an XML response to the request.

8  
9 45. The software code of claim 44, wherein individual objects that are  
10 instantiable by the software code are unique to an HTTP verb with which it  
11 corresponds.

12  
13 46. The software code of claim 44, wherein the object is configured to  
14 make calls to another object, the calls containing information that is to be included  
15 in the XML response.

16  
17 47. The software code of claim 44, wherein the object is configured to  
18 make calls to a second object, the calls containing information that is to be  
19 included in the XML response, the second object being configured to format the  
20 information into an appropriate syntactic form.